

Liebherr LTM 1095-5.1 (Y.O.M. 2014)

Used all-terrain crane - LIEBHERR model LTM 1095-5.1
(Max. lifting capacity - 95t; max. load moment - 300tm.)

Year of production: **2014**

Serial number.: **044254**

Registration plates no.: **WA 78260**

Millage: 47 490 km

Working hours: (as for 02.09.2025) // chassis: 3 349 mth // superstructure: 14 750 mth

Crane chassis:

5-axle Liebherr chassis with hydropneumatic suspension and NIVEUMATIK level control, LIEBHERR diesel engine with 370 kW (503 hp), exhaust emissions compliant with 97/68/EG and EPA/CARB, automatic transmission, two-range transfer case, 10 x 6 drive – all-wheel steering, 445/95 R 25 (16.00 R 25) tires, 2-circuit ZF steering system with active rear axle steering, all-wheel crab steering, 2-circuit pneumatic braking system. Maintenance-free axles, drive shafts, and suspension cylinders. Spacious, fully primed driver's cab (with CD radio). Hydraulic outriggers with permanently attached support discs, controlled via the BTT Bluetooth Terminal. Electronic inclination indicator and automatic leveling. Illuminated support points. Reversing audible alarm. Rear maneuvering coupling.

Crane superstructure:

Roller slewing ring, central lubrication system, LIEBHERR diesel engine with 129 kW (175 HP), emissions compliant with 97/68/EG and EPA/CABRB. Hydraulic system with two axial-piston pumps and a double gear pump, set to combine output. Winch, slewing, main boom, and telescoping with open hydraulic circuits, LOAD SENSING, electro-hydraulic crane control, oil cooler, 6-section boom from 12.5 m to 58 m with the TELEMATIK rapid telescoping system. The operator's cab is galvanized, tilts 20° backward, and includes a CD radio. 15 t of basic ballast + 8 t of additional ballast (up to 23 t total), with automatic ballasting from the operator's cab. Safety devices include a LICCON 2 overload protection system with electronic tilt indicator and standard software, a service diagnostic system, a LICCON work plan, and an anemometer.

Painting:

Two-tone

ADDITIONAL EQUIPMENT:

- Double swing-away jib 10,5m – 19,0m, mounted at angels of 0° / 20° / 40°
- Hook-Block 38,3 t, 3 rolls, 1 hook
- Hook-Block 16 t, 1 rolls, 1 hook

For PRICE (Incoterms EXW – PL); additional information & arranging for inspection; please follow the Contact details below:

Contact:

Andrzej Herfurt

tel.: (+48) 722 199 037

mail: andrzej.hurfurt@herkules-polska.pl



WWW.HERKULES-POLSKA.PL

+48 913 111 111



HERKULES S.A. w restrukturyzacji

ul. Annopol 5, 03-236 Warszawa

Dział Żurawi Warszawa
ul. Spokojna 19, 05-532 Baniocha

Biuro Gdańsk
ul. Trakt Św. Wojciecha 237A, 80-017 Gdańsk

Dział Żurawi Gdynia
ul. Hutnicza 1, 81-212 Gdynia

Sąd Rejonowy dla m. st. Warszawy w Warszawie, XIV Wydział Gospodarczy Krajowego Rejestru Sądowego. Kapitał zakładowy w wysokości 68 238 210,00 zł w pełni opłacony. KRS: 0000261094, NIP 9512032166, REGON 017433674



Contact:

Andrzej Herfurt

tel.: (+48) 722 199 037

mail: andrzej.hurfurt@herkules-polska.pl



WWW.HERKULES-POLSKA.PL

+48 913 111 111



HERKULES S.A. w restrukturyzacji

ul. Annopol 5, 03-236 Warszawa

Dział Żurawi Warszawa
ul. Spokojna 19, 05-532 Baniocza

Biuro Gdańsk
ul. Trakt Św. Wojciecha 237A, 80-017 Gdańsk

Dział Żurawi Gdynia
ul. Hutnicza 1, 81-212 Gdynia

Sąd Rejonowy dla m. st. Warszawy w Warszawie, XIV Wydział Gospodarczy Krajowego Rejestru Sądowego. Kapitał zakładowy w wysokości 68 238 210,00 zł w pełni opłacony. KRS: 0000261094, NIP 9512032166, REGON 017433674

+48 22 519 44 44 sekretariat@herkules-polska.pl